

H424

Key Specs

Weight Without Rotator and Link - 1105 kg
Maximum Feed Speed - 4.5–6.0 m/s
Maximum Roller Opening - 640 mm

Dimensions

Width, Head Open - 1570 mm
Width, Head Closed - 1290 mm
Height Without Rotator and Link - 1400 mm
Weight Without Rotator and Link - 1105 kg

Felling/Cutting

SuperCut 100S Saw Unit, Automatic Chain Tensioning - Standard
Length Of Saw Bar - 750 mm
Chain Type - 404
Chain Speed - 40 m/s

Feed System, Four-Wheel-Drive

Gross Feed Force - 400 / 620-cc motors: 27	315 / 503-cc motors: 21.5 kN
Maximum Feed Speed - 4.5–6.0 m/s	
Maximum Roller Opening - 640 mm	

Delimbing

Delimbing

Delimbing Knives - 4 moving, 2 fixed
Delimbing Diameter, Tip To Tip - 430 mm
Maximum Opening Upper Knives - 610 mm
Maximum Opening Lower Knives - 670 mm

Hydraulic System

Maximum Operating Pressure - 28 MPa
Recommended Pump Capacity - 200–340 L/min

Tank Capacities

Color Marking - Yes
Color Marking - 2.35 L
Chain Oil - 7.5 L
Chain Grease - 1.2 kg

Optional Equipment

Stump Treatment - Yes
Multi-Tree-Handling (MTH) - Yes
Mense Feed Rollers - Yes
Steel Thumbnail Feed Rollers - Yes
Steel V-Profile Feed Rollers - Yes
Steel Ribbed Feed Rollers - No
Chain And Saw Bar Kits - Yes
Hydraulic Hose Kit - Yes
Top Saw - No